





CitybeamLeb

5° narrow beam angle
 Astonishing level of brightness up to 250 meters
 High Power RGBW/FC 20W LEDs
 Energy efficient

To reach impressive heights, no matter how complex it is, the new CITYBEAM LED 12 is the right solution. Whatever is the final application, where long distance light output is required the CITYBEAM LED family solve your problem.

Standard fixture colour finishing is black, optional grey and white.

TECHNICAL FEATURES

• SOURCE

n. 12 RGBW (20W) LEDs 144W total light power

• OPTIC

5° (45 mm lenses)

On request:

- medium, wide 45 mm lenses
- TILT Manual 160°
- CONTROL

Standard interface: RS-485, optocoupled input

Protocol: USITT DMX512

CONNECTIONS

CYM simulation

Signal: 4pin IP 67 Amphenol connector (male-female)

Main Power: 3x1mm cable Available as accessories: - Wireless DMX receiver

SAFETY

n. 2 eyebolts for safety chains

• SETUP AND CONFIGURATION

Control panel with touch technology
Led display with flip function
Dedicated DMX channel for white balance
DMX or Auto mode with Master-Slave function
Intelligent temperature control
Flicker-free function
Smooth dimming function
Halogen simulation

• RATING PROTECTION
IP 67

• DMX CHANNELS

- 9CH mode

- 5CH mode

- 4CH mode

• POWER SUPPLY

Voltage range: 88-264VAC, 124-370VDC

Frequency range: 47-63Hz

Active Power factor:

PF>0.95/230VAC, PF>0.98/115VAC Current: 0.6A@230VAC; Fuse T5A Power: 150W (all color full power)

PHYSICAL

WxDxH: 355x185x420 mm

Weight: 12 Kg.



Click on the QR Code with your smartphone to go directly to the fixture website page

Studio Due

PHYSICAL















© Copyright 2014 **Studio Due light** srl Strada Poggino, 100 01100 Viterbo (Italy) tel. +39.0761.352520 (4 lines) fax +39.0761.352653 C.F. e P. IVA 05793121004